



Distributors Worldwide

1019 SE Holbrook Ct.
Port St. Lucie, FL 34952
772-335-8225 - Fax 772-335-3991
DUNS: 00-306-7852

Email: sales@enviroseal.com Web: <http://www.enviroseal.com>

RoofGuard™ general information and DIY installation instructions

Manufactured By:

Enviroseal Corporation.

1019 SE Holbrook Ct.

Port St. Lucie, FL, 34952

Phone: 772-335-8225

sales@enviroseal.com

www.enviroseal.com

US Patent No. 8,058,342

Product Description

RoofGuard™ is a patented 100% Acrylic Roof Coating designed to protect asphalt shingles, concrete and clay tile roof surfaces. It has been tested to Category Five hurricane force winds and prevents shingle damages. RoofGuard™ eliminates Granular Loss and Algae Growth with one application and can increase the life cycle of an asphalt shingle roof 5 to 7 years.

Typical Coverage Rates

Asphalt Shingles +/- 100 sf/ gallon

Concrete/Clay tile +/- 150 sf/gallon

Application rates will vary depending on porosity of surface, roof pitch, and application techniques.

Surface and Ground Preparation

Clean roof completely prior to application. Only experienced professionals should use high pressure water for cleaning. Remove dirt and algae with Roof Cleaner or bleach solution (1 part chlorine bleach and 2 parts water). Rinse thoroughly and allow to dry minimum 24 hours. Cover plants, concrete, or any other surface that could come into contact with RoofGuard™ prior to beginning.

Applying RoofGuard™

Apply with a pump sprayer, 1/2" nap roller, or airless paint sprayer (tip size 5-17 or larger). Apply RoofGuard™ uniformly until thoroughly saturated and adsorbed into the surface without runs. Back roll any runs immediately before drying. For increased durability, a second coat can be applied after the first coat has thoroughly dried.

Dry Time

Dry time depends on ambient weather conditions, usually 1 to 4 hours. Wind, temperature, sunlight, and humidity will determine actual dry time.

Cleaning Up

Clean tools and equipment immediately with water before RoofGuard™ dries. Once dry, RoofGuard™ will be very difficult to remove from any surface.

Important Product Information

Read entire label and understand instructions before using. Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period. Use NIOSH approved eye and respiratory protection, gloves, long pants, and long sleeves when applying RoofGuard™. Do not apply if rain is imminent or forecast within 24 hours of application.

Environmental, Use, and Safety Considerations

- Refer To complete instructions prior to use
- Close Container When Not In Use
- Refer to Safety Data Sheet (SDS) for Environmental Information
- VOC 142 Grams/Liter (EPA # 24)
- Keep Out Of Reach of Children
- Avoid Breathing Vapors or mist and Contact With Eyes and Skin
- Use NIOSH approved eye and respiratory protection
- Dispose of unused material in accordance with local, State and Federal laws
- Do Not Store Below 40 °F
- Do Not dilute with water
- Do Not Freeze

Warranty

Enviroseal warrants against loss of granular and algae growth for five years when installed by a certified contractor, contact Enviroseal for further information. Satisfactory results depend not only upon quality products but also upon many factors beyond our control. The information contained herein is generalized and may not be applicable for all installations. RoofGuard™ is warranted to be of uniform quality within manufacturing tolerances. Enviroseal has no control over the use of this Product upon receipt of customer and customer agrees to assume full responsibility for each application and Enviroseal assumes no liability for final results. Refer to published terms and conditions prior to use.

Rev-Feb. 2016